

AMENDMENTS TO THE CLAIMS:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method for constructing a high rise building having a core and a residence space around the core, the method comprising the steps of:
 - (a) installing a steel-frame pillar on a shaft portion of the core;
 - (b) connecting a girder to the steel-frame pillar, the girder includes an anchor-connecting member to which a steel-frame beam is connected, a portion of the anchor-connecting member being buried in a ~~core-wall~~ of the core;
 - (c) assembling the steel-frame beam on the anchor-connecting member;
 - (d) ~~installing~~ arranging a reinforcing bar in a deck plate or a slab type mold ~~installed on the steel-frame beam, and mounting a reinforcing bar on the~~ a-wall of the core; and
 - (e) applying concrete for a slab and concrete for the wall of the core simultaneously or in this order.

2. (Currently Amended) The method of claim 1, further comprising the step of:
installing a wherein plural sub-connecting member members for supporting the deck plate ~~or the slab type mold are installed on the girder installed between~~ more than one the steel-frame pillarpillars, the sub-connecting member comprises ~~members including a~~ connecting member coupled to the girder and a supporting

member coupled to one end of the connecting member.

3. (Currently Amended) The method of claim 1, wherein the anchor-connecting member comprises a connecting member connected to the girder by welding or bolts, an anchor plate connected to the connecting member by welding or bolts, a gusset plate welded on the anchor plate, and a stud or shear connector extended from the anchor plate to a ~~the~~ concrete wall and buried in ~~the~~ concrete.

4. (Previously Presented) The method of claim 1, wherein the step (c) further comprises the steps of forming a slot hole on the anchor-connecting member and coupling a high tensioned bolt in the slot hole to be assembled on the steel-frame beam.

5. (New) The method of claim 2, wherein the deck plate is supported by the sub-connecting member and located adjacent to a top side of the sub-connecting member.